

533,748

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/048903 A1

(51) International Patent Classification⁷: **G01F 1/66**,
G01P 5/00

(21) International Application Number:
PCT/NL2002/000762

(22) International Filing Date:
25 November 2002 (25.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **INSTROMET ULTRASONICS B.V.** [NL/NL]; 61, Pieter Zeemanweg, NL-3316 GZ Dordrecht (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BOTTER, Eduard, Johannes** [NL/NL]; 120, Herenstraat, NL-2291 BK Watertingen (NL).

(74) Agent: **VOLMER, J., C.**; Exter Polak & Charlouis B.V., P.O. Box 3241, NL-2280 Ge Rijswijk (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **ULTRASONIC SIGNAL PROCESSING METHOD AND APPLICATIONS THEREOF**



(57) Abstract: An ultrasonic signal processing method for improving the signal-to-noise ratio in ultrasonic measurements comprises the transmission of a predefined timed sequence of a number of ultrasonic burst signals at a first transducer, and reception of a signal representing said transmitted sequence of ultrasonic burst signals at a second transducer. This signal is processed by addition of multiple time-shifted copies of the received signal to said original received signal to obtain a sum of the original received signal and its time-shifted copies. An original burst signal having an improved signal-to-noise ratio is reconstructed from this sum.

WO 2004/048903 A1

